

Growatt SPF 3000~5000TL HVM

- Integrated MPPT charge controller
- Configurable grid or solar input priority
- Optional WIFI/ GPRS remote monitoring
- Parallel for scalability



powering tomorrow
Growatt

www.ginverter.com

P O W E R
- I N G
T O M O R R O W

Datasheet	SPF 3000TL HVM-24	SPF 3000TL HVM-48	SPF 5000TL HVM/HVM-P
Battery voltage	24VDC	48VDC	48VDC

INVERTER OUTPUT

RATED POWER	3000VA/ 3000W	3000VA/ 3000W	5000VA/ 5000W
Parallel Capability	No	No	Yes, 6 units
AC Voltage Regulation (Battery Mode)	230VAC \pm 5% @ 50/60Hz	230VAC \pm 5% @ 50/60Hz	230VAC \pm 5% @ 50/60Hz
Surge Power	6000VA	6000VA	10000VA
Efficiency (Peak)	93%	93%	93%
Waveform	Pure sine wave	Pure sine wave	Pure sine wave
Transfer Time	10 ms (For Personal Computers); 20 ms (For Home Appliances)		

SOLAR CHARGER

Maximum PV Array Power	1000W	2400W	4500W
MPPT Range @ Operating Voltage	30VDC ~ 80VDC	60VDC ~ 115VDC	60VDC ~ 115VDC
Maximum PV Array Open Circuit Voltage	100VDC	145VDC	145VDC
Maximum Solar Charge Current	50A	40A	80A
Maximum Efficiency	97%	97%	97%
Standby Power Consumption	2 W	2 W	2 W

AC CHARGER

Charge Current	30A	15A	60A
AC Input Voltage	230 VAC	230 VAC	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)		
Frequency Range	50Hz/60Hz (Auto sensing)	50Hz/60Hz (Auto sensing)	50Hz/60Hz (Auto sensing)

PHYSICAL

Dimension (D/W/H) in mm	120/315/390	120/315/390	130/350/455
Net Weight (kgs)	8	8	14.5

OPERATING ENVIRONMENT

Humidity	5% to 95% Relative Humidity(Non-condensing)	5% to 95% Relative Humidity(Non-condensing)	5% to 95% Relative Humidity(Non-condensing)
Operating Temperature	0°C - 55°C	0°C - 55°C	0°C - 55°C
Storage Temperature	-15°C - 60°C	-15°C - 60°C	-15°C - 60°C